


Highest permissible loads in concrete C20/25

Multiple use for non-structural applications. Total safety factor as per ETAG 001 included (γ_M and γ_F). The maximum load per fixing point for multiple use for non-structural applications may, depending on national regulations, are below the approved load of the anchor. The approved loads per fixing point are regulated for their respective countries in the ETAG 001, Part 6.

Loads and performance data	Nail anchor steel, zinc plated		ENA-K	
			cracked/non-cracked concrete	
Effective anchorage depth	h_{ef}	[mm]	25	30
Approved loads (Picture 1)	C12/15 appr. F	[kN]	1,43	1,90
	C20/25 - C50/60 appr. F	[kN]	2,14	2,81
Approved loads (Picture 2)	C12/15 appr. F	[kN]	0,71	0,95
	C20/25 - C50/60 appr. F	[kN]	0,95	1,19
Approved bending moments	appr. M	[Nm]	7,3	7,7
Minimum thickness of concrete slab	h_{min}	[mm]	80	80
Installation parameters				
Drill hole diameter	d_o	[mm]	6	6
Diameter of clearance hole in the fixture	d_r	[mm]	7	7
Diameter nailhead		[mm]	13	13
Depth of drill hole	h_1	[mm]	35	40
Installation torque	$\leq T_{inst}$	[Nm]	-	-

Picture 1: maximum loads



Picture 2: minimum spacing and edge distance

